

## Stainless Steel Spring Retractable Reels

JARCH's stainless steel hose reels are ideal for food processing, pre-rinse, wash down, chemical transfer and industrial-solvent handling. Also suitable for coastal, offshore and on-board ship in marine applications where the harsh environment of salt water spray requires the use of stainless steel hose reels.



LC807 OLS-S



D9300 OLSBW



HS18000 L



3900-23-20-15FFSS

### Features:

- \* The bracket and the reel are stamped and molded, the whole is light and strong, and the strength is firm.
- \* 304 stainless steel surface, electrochemical treatment of the overall corrosion resistance, anti oil pollution;
- \* 500000 life revolving joint.

Model without hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Pressure		NPT(F) Outlet	NPT(F) Inlet
	lbs	kg	in	mm	in	mm		m	psi	bar	in	in
Low and Medium Pressure Reels      Maximum temperature 210 °F (99 °C)												
LC600 OLS-S	33	15	3/8	10	.591	15	50	15	300	21	3/8	3/8
LC607 OLS-S	35	16	3/8	10	.591	15	70	21	300	21	3/8	3/8
LC800 OLS-S	33	15	1/2	13	.750	19	50	15	300	21	1/2	1/2
LC807 OLS-S	37	17	1/2	13	.750	19	70	21	300	21	1/2	1/2
LC905 OLS	40	18	3/4	19	1.063	27	50	15	300	21	3/4	3/4
D9300 OLSSW	99	45	3/4	19	1.181	30	77	23	300	21	3/4	3/4
D9300 OLSBW	117	53	3/4	19	1.181	30	77	23	500	35	3/4	3/4
D9400 OLSBW	117	53	1	25	1.514	38	50	15	500	35	1	1
N9300 OLSSW	117	53	3/4	19	1.181	30	77	20	300	21	3/4	3/4
N9400 OLSSW	117	53	1	25	1.514	38	50	15	500	35	1	1
3900-23-20-15FFSS	95	42	1 1/2	38	2.06	52	95	29	300	21	1 1/2	1 1/2
HS18000 L	33	15	1/2	13	.750	19	203	61	300	21	1/2	1/2
HS18000 M	35	16	1/2	13	.750	19	203	61	3000	207	1/2	1/2
HS19000 L	33	15	3/4	19	1.063	27	90	27	300	21	3/4	3/4
HS19000 M	37	17	3/4	19	1.181	30	90	27	3000	207	3/4	3/4

Note: stainless steel reel needs customized hose.